January 2012 Back@Basics Solution

Based on Cx-3 ATC/FPT software

Month 1: Energy Retro-CX Airside			Mode:			On-100% Occupancy & Max Cooling 2		On-50% Occupancy & Nominal Cooling 3	
- New ERU & DOAS application		Status:							
Device	Tag	Description	Reaction	Status	Result	Status	Result	Status	Result
	BAS Computer	Building Automation System Interface	Monitoring Normal power Emergency power Alarm indication Occupied cycle Unoccupied cycle	x x x	Pass/Fail Pass/Fail Pass/Fail	x x x	Pass/Fail Pass/Fail Pass/Fail	x x x	Pass/Fail Pass/Fail Pass/Fail
Q++ D-1	D-1	2-Position OA Damper	Closed Open	X X	Pass/Fail Pass/Fail	x	Pass/Fail	x	Pass/Fail
SAF-1	SAF-1	Supply Air Fan	On Off Modulating	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
F-1 DOAS	F-1 DOAS	BFilter Differential Pressure	No signal Monitoring High static- dirty filter	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
UV-1st	UV-1ST	1st Unit Ventilator	On Off	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
UV-Last	UV-LAST	Last Unit Ventilator	On Off	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
UV-Typ	UV-TYP	Typical Unit Ventilator	On Off	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
CC-1	CC-1	Cooling Coil With 2-way ATC Valve	Closed Open Modulating	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
PHC-1	PHC-1	Pre-Heating Coil With 2-way ATC Valve	Closed Open Modulating	x	Pass/Fail	х	Pass/Fail	x	Pass/Fail
RHC-1 成	RHC-1	Reheating Coil With 2-way ATC Valve	Closed Open Modulating	x	Pass/Fail	х	Pass/Fail	x	Pass/Fail
ERC- DOAS	ERC-DOAS	Energy Recovery Coil	No flow Full flow	x	Pass/Fail	x	Pass/Fail	x	Pass/Fail
CHWP-1	CHWP-1	CHW Pump VFD	On Off Modulating	x	Pass/Fail	x	Pass/Fail	x x	Pass/Fail Pass/Fail